



Product Service

# CERTIFICATE

No. Z1A 090658 0090 Rev. 00

**Holder of Certificate:** Flokk Sp.z o.o.

Gornicza 8  
62-700 Turek  
POLAND

**Certification Mark:**



**Product:** Office chairs

**Tested according to:** DIN EN 1335-1:2020  
DIN EN 1335-2:2019  
AfPS GS 2019:01 PAK  
PPP 51054C:2021

With this certificate, in its capacity as a notified GS body, TÜV SÜD Product Service GmbH issues the GS Mark to the named certificate holder for the declared product with the named model designation in accordance with section 20 ProdSG (German Product Safety Act). The product meets the safety and health requirements of section 20 (3) ProdSG. The manufacturer is reminded of their obligations in accordance with section 24 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition, the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 713266694

**Valid until:** 2027-10-27

**Date,** 2022-10-28

( Jens Biesenack )

# CERTIFICATE

No. Z1A 090658 0090 Rev. 00

**Model(s):** giroflex 40, 40-4049

**Parameters:**

Seat support	Synchronously seat inclination plus separate tilt adjustment, seat adjustable in depth.
Height adjustment	Seat height adjustment by means of gas pressure spring. Manufacturer Qingdao Aode Precision Instrument Co. Ltd., Tube-type: SKQ-A/B-25, Material: Q235B, Wall thickness: 2.5 mm, Surface: hard chrome, class 4 according to EN16955:2017
Seat surface	Plastic seat shell, upholstered seat.
Backrest	Backrest frame made of plastic, mesh backrest surface with textile cover, lumbar support with depth and height adjustment. The backrest is fixed in height.
Armrests	Plastic armrests that are adjustable in the height. The pads are adjustable in front / rear and inwards / outwards.
Base	Aluminium or plastic base, Ø 720 mm
Castors	Load-dependent braked double castors Ø 65 mm, type "H" for soft floors or type "W" for hard floors.
Chair type	B (according to DIN EN 1335-1:2020)