

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

giroflex 64









Flol: l:

The Norwegian EPD Foundation

Owner of the declaration:

Flokk AS

Product:

giroflex 64

Declared unit:

1 pcs

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core

NPCR 026:2022 Part B for Furniture

Program operator:

The Norwegian EPD Foundation

Declaration number:

NEPD-4981-4340-EN

Registration number:

NEPD-4981-4340-EN

Issue date: 18.09.2023

Valid to: 18.09.2028

EPD Software:

LCA.no EPD generator ID: 69249



General information

Product

giroflex 64

Program operator:

Post Box 5250 Majorstuen, 0303 Oslo, Norway The Norwegian EPD Foundation Phone: +47 23 08 80 00 web: post@epd-norge.no

Declaration number: NEPD-4981-4340-EN

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR NPCR 026:2022 Part B for Furniture

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 pcs giroflex 64

Declared unit (cradle to gate) with option:

A1-A3,A4,A5,B2,B3,B4,C1,C2,C3,C4,D

Functional unit:

giroflex 64-3578 with 1D armrest (Powder coating parts, Xtreme/Camira - Including packaging

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Norway's guidelines for verification and approval requiring that tools are i integrated into the company's environmental management system, ii the procedures for use of the EPD tool are approved by EPD-Norway, and iii the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPDNorway's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects (no signature required

Owner of the declaration:

Flokk AS Contact person: Atle Thiis-Messel Phone: 0047 98 25 68 30 e-mail: atle.messel@flokk.com

Manufacturer:

Flokk AS Drammensveien 145, 0277 Oslo, Norway

Place of production:

Flokk - Turek ul. Górnicza 8 62-700 Turek, Poland

Management system:

ISO 14001, ISO 9001, ISO 50001 (Norway, Sweden

Organisation no:

No 928 902 749

Issue date: 18.09.2023

Valid to: 18.09.2028

Year of study:

2022

Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.

Developer of EPD: Damian Bakowski

Reviewer of company-specific input data and EPD: Monika Kuczynska

Approved:

Håkon Hauan, CEO EPD-Norge



Product

Product description:

The giroflex 64 – Swivel chair: Available with standard or comfort upholstery in various seat widths and backrest heights, as well as optionally with depth-adjustable lumbar support. Diverse cover materials in various colours. Available with fixed, height-adjustable or 4D armrests and coathanger. Optionally with covered back shell and padded armrests. 5-arm base with choice of polished or powder-coated aluminium in diverse colours. Castors ø 50 mm or optionally ø 65 mm.

Product specification

giroflex 64-3578 dimensions:

Seat height: 40-52 cm Overall height: 100-119 Overal width: 66 Seat depth: 41,5-44

Total weight: 21,67 kg (packaging excluded) Total weight: 27,15 kg (packaging included)

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Others	0,05	0,25	0,00	1,24
Plastic - Polyoxymethylene (POM)	0,22	1,03	0,00	0,00
Metal - Steel	5,08	23,46	1,02	19,97
Metal - Aluminium	8,84	40,77	8,84	100,00
Adhesive	0,63	2,91	0,01	1,82
Plastic - Polypropylene (PP)	1,13	5,23	0,00	0,00
Plastic - Nylon (PA)	2,84	13,11	0,00	0,00
Rubber, synthetic	0,01	0,03	0,00	0,00
Powder coating	0,22	1,02	0,00	0,00
Plastic - Polyurethane (PUR)	1,95	8,98	0,00	0,00
Plastic - Polyethylene (HDPE)	0,01	0,03	0,00	0,00
Textile - Polyester (PE)	0,69	3,17	0,69	99,96
Total	21,67		10,55	

Packaging	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Packaging - Plastic	0,19	3,52	0,00	0,00
Recycled cardboard	4,28	78,13	4,28	100,00
Packaging - Paper	1,01	18,35	0,35	34,31
Total incl. packaging	27,15		15,18	

Technical data:

The model studied in detail in this declaration is the giroflex 64-3578 with 4D armrest (Powder coating parts, Camira/Xtreme, Including packaging). The key environmental indicators for the other models and options of the giroflex 64 collection are presented on a table page 12 of this declaration.

Market:

Worldwide

Reference service life, product

5 years

Reference service life, building

LCA: Calculation rules

Declared unit:

1 pcs giroflex 64

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.



Data quality:


Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Metal - Aluminium	ecoinvent 3.6	Database	2019
Metal - Steel	ecoinvent 3.6	Database	2019
Others	ecoinvent 3.6	Database	2019
Packaging - Paper	ecoinvent 3.6	Database	2019
Packaging - Plastic	ecoinvent 3.6	Database	2019
Plastic - Nylon (PA)	ecoinvent 3.6	Database	2019
Plastic - Polyethylene (HDPE)	ecoinvent 3.6	Database	2019
Plastic - Polyoxymethylene (POM)	ecoinvent 3.6	Database	2019
Plastic - Polypropylene (PP)	ecoinvent 3.6	Database	2019
Plastic - Polyurethane (PUR)	ecoinvent 3.6	Database	2019
Powder coating	Ecoinvent 3.6	Database	2019
Rubber, synthetic	ecoinvent 3.6	Database	2019
Textile - Polyester (PE)	ecoinvent 3.6	Database	2019
Recycled cardboard	Modified ecoinvent 3.6	Database	2019
Textile - Polyester (PE)	Modified ecoinvent 3.6	Database	2019
Adhesive	Modified ecoinvent 3.6	Database/Supplier	2019

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Р	roduct stag	ge		uction on stage	Use stage End of life stage						Beyond the system boundaries					
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De- construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery- Recycling-potential
A1	A2	A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	C3	C4	D
Χ	Χ	Χ	Χ	Χ	MND	X	Χ	Χ	MND	MND	MND	Χ	X	X	Χ	X

System boundary:



Additional technical information:



LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 5 (km)	53,3 %	1000	0,023	l/tkm	23,00
Assembly (A5)	Unit	Value			
Waste, packaging, cardboard, 100 % recycled, to average treatment (kg)	kg	4,28			
Waste, packaging, paper printed, to average treatment (kg)	kg	1,01			
Waste, packaging, plastic film (LDPE), to average treatment - A5 (kg)	kg	0,19			
Maintenance (B2)	Unit	Value			
Electricity, European average (kWh)	kWh/DU	10,53			
Electricity, World average (kWh)	kWh/DU	1,17			
Water, tap water (m3)	m3/DU	0,78			
Repair (B3)	Unit	Value			
Electricity, European average (kWh)	kWh/DU	0,50			
Electricity, World average (kWh)	kWh/DU	0,06			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 5 (km)	36,7 %	85	0,044	l/tkm	3,74
Waste processing (C3)	Unit	Value			
Waste treatment per kg Hazardous waste,	len.	0.63			
incineration (kg)	kg	0,63			
Waste treatment per kg Non-hazardous waste, incineration with fly ash extraction - C3 (kg)	kg	1,41			
Waste treatment per kg Plastics, Mixture, municipal incineration with fly ash extraction (kg)	kg	1,65			
Waste treatment per kg Polyethylene, PE, incineration with fly ash extraction - C3 (kg)	kg	0,01			
Waste treatment per kg Polyoxymethylene (POM), incineration with fly ash extraction (kg) - CH - C3	kg	0,22			
Waste treatment per kg Polypropylene (PP), incineration with fly ash extraction - C3 (kg)	kg	1,13			
Waste treatment per kg Polyurethane (PU), incineration (kg)	kg	1,95			
Waste treatment per kg Rubber, municipal incineration with fly ash extraction (kg)	kg	0,01			
Waste treatment per kg Scrap aluminium, incineration with fly ash extraction (kg)	kg	8,84			
Waste treatment per kg Scrap steel, incineration with fly ash extraction (kg)	kg	5,08			
Waste treatment per kg Textile, incineration with fly ash extraction (kg)	kg	0,69			
Waste, materials to recycling (kg)	kg	2,64			

Flol: l:

Disposal (C4)	Unit	Value		
Landfilling of ashes and residues from incineration of Scrap aluminium (kg)	kg	7,92		
Landfilling of ashes and residues from incineration of Scrap steel (kg)	kg	3,37		
Landfilling of ashes from incineration of Hazardous waste, from incineration (kg)	kg	0,12		
Landfilling of ashes from incineration of Non- hazardous waste, process per kg ashes and residues - C4 (kg)	kg	0,33		
Landfilling of ashes from incineration of Plastics, Mixture, municipal incineration with fly ash extraction, process per kg ashes and residues - C4 (kg)	kg	0,06		
Landfilling of ashes from incineration of Polyethylene, PE, process per kg ashes and residues - C4 (kg)	kg	0,00		
Landfilling of ashes from incineration of Polyoxymethylene (POM), process per kg ashes and residues (kg) - CH - C4	kg	0,00		
Landfilling of ashes from incineration of Polypropylene, PP, process per kg ashes and residues - C4 (kg)	kg	0,03		
Landfilling of ashes from incineration of Polyurethane (PU), process per kg ashes and residues - C4 (kg)	kg	0,07		
Landfilling of ashes from incineration of Rubber, process per kg ashes and residues - C4 (kg)	kg	0,00		
Landfilling of ashes from incineration of Textile, soiled, process per kg ashes and residues (kg)	kg	0,03		

Benefits and loads beyond the system boundaries (D)	Unit	Value		
Substitution of electricity, in Norway (MJ)	MJ	8,84		
Substitution of primary steel with net scrap (kg)	kg	1,40		
Substitution of thermal energy, district heating, in Norway (MJ)	МЈ	133,73		



LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environme	ental impact							
	Indicator	Uni	t	A1-A3	A4	A5	B2	В3
	GWP-total	kg CO ₂	-eq	7,91E+01	2,47E+00	9,11E+00	5,67E+00	2,54E-01
	GWP-fossil	kg CO ₂	kg CO ₂ -eq		2,47E+00	1,01E-01	5,62E+00	2,52E-01
	GWP-biogenic	kg CO ₂	kg CO ₂ -eq		1,01E-03	9,01E+00	3,61E-02	1,62E-03
	GWP-luluc	kg CO ₂	-eq	1,02E-01	7,20E-04	2,95E-05	1,27E-02	5,74E-04
٨	ODP	kg CFC1	1 -eq	5,13E-06	5,70E-07	1,90E-08	4,39E-07	1,95E-08
	АР	mol H+	eq	4,32E-01	1,04E-02	4,24E-04	3,22E-02	1,44E-03
	EP-FreshWater	kg P -	eq	4,47E-03	1,88E-05	7,34E-07	5,47E-04	2,47E-05
4	EP-Marine	kg N	eq	1,05E-01	3,12E-03	1,51E-04	4,31E-03	1,91E-04
*	EP-Terrestial	mol N	-eq	8,98E-01	3,45E-02	1,52E-03	5,22E-02	2,32E-03
	POCP	kg NMV0	OC -eq	2,92E-01	1,11E-02	4,39E-04	1,35E-02	5,94E-04
	ADP-minerals&metals ¹	kg Sb	-eq	3,72E-02	4,21E-05	2,16E-06	4,34E-05	1,69E-06
	ADP-fossil ¹	М		1,33E+03	3,84E+01	1,26E+00	1,08E+02	4,87E+00
<u>%</u>	WDP ¹	m ³		1,66E+04	2,94E+01	1,74E+00	1,51E+03	6,70E+01
	Indicator	Unit	B4	C1	C2	C3	C4	D
(P)				CI	CZ	CS	C4	D
	GWP-total	kg CO ₂ -eq	0	0	3,85E-01	1,83E+01	1,83E-01	-2,34E+00
	GWP-total GWP-fossil	kg CO ₂ -eq						
			0	0	3,85E-01	1,83E+01	1,83E-01	-2,34E+00
	GWP-fossil	kg CO ₂ -eq	0	0	3,85E-01 3,85E-01	1,83E+01 1,73E+01	1,83E-01 1,83E-01	-2,34E+00 -2,31E+00
	GWP-fossil GWP-biogenic	kg CO ₂ -eq	0 0 0	0 0 0	3,85E-01 3,85E-01 1,57E-04	1,83E+01 1,73E+01 1,01E+00	1,83E-01 1,83E-01 1,21E-04	-2,34E+00 -2,31E+00 -2,45E-03
	GWP-fossil GWP-biogenic GWP-luluc	kg CO ₂ -eq kg CO ₂ -eq kg CO ₂ -eq	0 0 0 0	0 0 0	3,85E-01 3,85E-01 1,57E-04 1,34E-04	1,83E+01 1,73E+01 1,01E+00 4,78E-04	1,83E-01 1,83E-01 1,21E-04 4,40E-05	-2,34E+00 -2,31E+00 -2,45E-03 -2,74E-02
	GWP-fossil GWP-biogenic GWP-luluc ODP	kg CO ₂ -eq kg CO ₂ -eq kg CO ₂ -eq kg CFC11 -eq	0 0 0 0 0 0	0 0 0 0	3,85E-01 3,85E-01 1,57E-04 1,34E-04 8,77E-08	1,83E+01 1,73E+01 1,01E+00 4,78E-04 2,28E-07	1,83E-01 1,83E-01 1,21E-04 4,40E-05 4,23E-08	-2,34E+00 -2,31E+00 -2,45E-03 -2,74E-02 -5,65E-02
	GWP-fossil GWP-biogenic GWP-luluc ODP AP	kg CO ₂ -eq kg CO ₂ -eq kg CO ₂ -eq kg CFC11 -eq mol H+ -eq	0 0 0 0 0	0 0 0 0 0	3,85E-01 3,85E-01 1,57E-04 1,34E-04 8,77E-08 1,57E-03	1,83E+01 1,73E+01 1,01E+00 4,78E-04 2,28E-07 9,53E-03	1,83E-01 1,83E-01 1,21E-04 4,40E-05 4,23E-08 1,02E-03	-2,34E+00 -2,31E+00 -2,45E-03 -2,74E-02 -5,65E-02 -1,40E-02
	GWP-fossil GWP-biogenic GWP-luluc ODP AP EP-FreshWater	kg CO ₂ -eq kg CO ₂ -eq kg CO ₂ -eq kg CFC11 -eq mol H+ -eq kg P -eq	0 0 0 0 0 0	0 0 0 0 0 0	3,85E-01 3,85E-01 1,57E-04 1,34E-04 8,77E-08 1,57E-03 3,02E-06	1,83E+01 1,73E+01 1,01E+00 4,78E-04 2,28E-07 9,53E-03 4,05E-05	1,83E-01 1,83E-01 1,21E-04 4,40E-05 4,23E-08 1,02E-03 1,82E-06	-2,34E+00 -2,31E+00 -2,45E-03 -2,74E-02 -5,65E-02 -1,40E-02 -1,64E-04
	GWP-fossil GWP-biogenic GWP-luluc ODP AP EP-FreshWater EP-Marine	kg CO ₂ -eq kg CO ₂ -eq kg CO ₂ -eq kg CFC11 -eq mol H+ -eq kg P -eq kg N -eq	0 0 0 0 0 0	0 0 0 0 0 0	3,85E-01 3,85E-01 1,57E-04 1,34E-04 8,77E-08 1,57E-03 3,02E-06 4,66E-04	1,83E+01 1,73E+01 1,01E+00 4,78E-04 2,28E-07 9,53E-03 4,05E-05 4,29E-03	1,83E-01 1,83E-01 1,21E-04 4,40E-05 4,23E-08 1,02E-03 1,82E-06 3,51E-04	-2,34E+00 -2,31E+00 -2,45E-03 -2,74E-02 -5,65E-02 -1,40E-02 -1,64E-04 -3,67E-03
	GWP-fossil GWP-biogenic GWP-luluc ODP AP EP-FreshWater EP-Marine EP-Terrestial	kg CO ₂ -eq kg CO ₂ -eq kg CO ₂ -eq kg CFC11 -eq mol H+ -eq kg P -eq kg N -eq mol N -eq	0 0 0 0 0 0 0	0 0 0 0 0 0 0	3,85E-01 3,85E-01 1,57E-04 1,34E-04 8,77E-08 1,57E-03 3,02E-06 4,66E-04 5,16E-03	1,83E+01 1,73E+01 1,01E+00 4,78E-04 2,28E-07 9,53E-03 4,05E-05 4,29E-03 4,31E-02	1,83E-01 1,83E-01 1,21E-04 4,40E-05 4,23E-08 1,02E-03 1,82E-06 3,51E-04 3,90E-03	-2,34E+00 -2,31E+00 -2,45E-03 -2,74E-02 -5,65E-02 -1,40E-02 -1,64E-04 -3,67E-03 -3,88E-02
	GWP-fossil GWP-biogenic GWP-luluc ODP AP EP-FreshWater EP-Marine EP-Terrestial POCP	kg CO ₂ -eq kg CO ₂ -eq kg CO ₂ -eq kg CFC11 -eq mol H+ -eq kg P -eq kg N -eq mol N -eq kg NMVOC -eq	0 0 0 0 0 0 0 0	0 0 0 0 0 0 0	3,85E-01 3,85E-01 1,57E-04 1,34E-04 8,77E-08 1,57E-03 3,02E-06 4,66E-04 5,16E-03 1,58E-03	1,83E+01 1,73E+01 1,01E+00 4,78E-04 2,28E-07 9,53E-03 4,05E-05 4,29E-03 4,31E-02 1,06E-02	1,83E-01 1,83E-01 1,21E-04 4,40E-05 4,23E-08 1,02E-03 1,82E-06 3,51E-04 3,90E-03 1,12E-03	-2,34E+00 -2,31E+00 -2,45E-03 -2,74E-02 -5,65E-02 -1,40E-02 -1,64E-04 -3,67E-03 -3,88E-02 -1,39E-02

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment: EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

Remarks to environmental impacts

[&]quot;Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"

^{*}INA Indicator Not Assessed

^{1.} The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator



Additional er	Additional environmental impact indicators										
	Indicator	Unit		A1-A3	A4	A5	B2	В3			
	PM	Disease incidence		4,99E-06	2,17E-07	6,31E-09	1,14E-07	4,75E-09			
	IRP ²	kgBq U235 -eq		3,25E+00	1,68E-01	5,41E-03	8,90E-01	4,03E-02			
	ETP-fw ¹	CTUe		2,26E+03	2,81E+01	1,66E+00	8,66E+01	3,84E+00			
44.2	HTP-c ¹	CTUh		1,57E-07	0,00E+00	4,80E-11	2,79E-09	9,70E-11			
4% B	HTP-nc ¹	CTUh		1,87E-06	2,72E-08	2,06E-09	8,81E-08	3,37E-09			
	SQP ¹	dimensionless		8,06E+02	4,40E+01	9,13E-01	2,53E+01	1,13E+00			
I	ndicator	Unit	B4	C1	C2	C3	C4	D			
	PM	Disease incidence	0	0	2,77E-08	7,84E-08	1,73E-08	-5,15E-07			
	IRP ²	kgBq U235 -eq	0	0	2,54E-02	3,60E-02	1,32E-02	-6,53E-02			
	ETP-fw ¹	CTUe	0	0	4,27E+00	1,06E+02	2,49E+00	-1,46E+02			
44. ** <u>:</u> <u>B</u>	HTP-c ¹	CTUh	0	0	0,00E+00	2,67E-09	1,00E-10	-8,50E-09			
₩ <u></u>	HTP-nc ¹	CTUh	0	0	4,62E-09	4,74E-08	3,15E-09	1,03E-07			
&	SQP ¹	dimensionless	0	0	4,00E+00	2,96E+00	7,08E+00	-7,51E+01			

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)

[&]quot;Reading example: 9,0 E-03 = 9,0*10-3 = 0,009"

^{*}INA Indicator Not Assessed

^{1.} The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

^{2.} This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Flol: l:

Resource use									
34 3	Indicator		U	nit	A1-A3	A4	A5	B2	В3
Ë	PERE		MJ		1,61E+02	4,83E-01	2,13E-02	1,99E+01	9,05E-01
	PERM		MJ		4,93E+01	0,00E+00	-3,93E+01	0,00E+00	0,00E+00
₽ ,	PERT		N	MJ		4,83E-01	-3,92E+01	1,99E+01	9,05E-01
A	PENRE		N	MJ	1,14E+03	3,84E+01	1,26E+00	1,08E+02	4,88E+00
Åg	PENRM		N	MJ	2,08E+02	0,00E+00	-8,19E+00	0,00E+00	0,00E+00
IA	PENRT		N	MJ	1,35E+03	3,84E+01	-6,93E+00	1,08E+02	4,88E+00
	SM		k	кg	1,52E+01	0,00E+00	0,00E+00	0,00E+00	0,00E+00
2	RSF		N	WJ	1,84E+00	1,69E-02	6,95E-04	1,38E+00	6,27E-02
	NRSF		МЈ		3,39E+00	5,66E-02	2,80E-03	3,70E-01	1,51E-02
<u>%</u>	FW		m ³		1,62E+00	4,37E-03	5,98E-04	8,69E-01	3,99E-03
Indi	cator	U	Jnit	B4	C1	C2	C3	C4	D
India C	cator PERE		Jnit MJ	B4 0	C1 0	C2 8,19E-02	C3 1,24E+00	C4 8,57E-02	D -6,95E+01
		ı							
T T	PERE	1	МЈ	0	0	8,19E-02	1,24E+00	8,57E-02	-6,95E+01
I	PERE PERM	1	W1 W1	0	0	8,19E-02 0,00E+00	1,24E+00 0,00E+00	8,57E-02 0,00E+00	-6,95E+01 0,00E+00
₽	PERE PERM PERT	1	MJ MJ	0 0	0 0	8,19E-02 0,00E+00 8,19E-02	1,24E+00 0,00E+00 1,24E+00	8,57E-02 0,00E+00 8,56E-02	-6,95E+01 0,00E+00 -6,95E+01
3 4	PERE PERM PERT PENRE	1	MJ MJ MJ	0 0 0	0 0 0	8,19E-02 0,00E+00 8,19E-02 5,80E+00	1,24E+00 0,00E+00 1,24E+00 1,04E+01	8,57E-02 0,00E+00 8,56E-02 3,19E+00	-6,95E+01 0,00E+00 -6,95E+01 -2,40E+01
E I I I	PERE PERM PERT PENRE PENRM	1	мл мл мл мл	0 0 0 0	0 0 0 0	8,19E-02 0,00E+00 8,19E-02 5,80E+00 0,00E+00	1,24E+00 0,00E+00 1,24E+00 1,04E+01 -1,99E+02	8,57E-02 0,00E+00 8,56E-02 3,19E+00 0,00E+00	-6,95E+01 0,00E+00 -6,95E+01 -2,40E+01 0,00E+00
	PERE PERM PERT PENRE PENRM PENRT		мл мл мл мл	0 0 0 0 0	0 0 0 0 0	8,19E-02 0,00E+00 8,19E-02 5,80E+00 0,00E+00 5,80E+00	1,24E+00 0,00E+00 1,24E+00 1,04E+01 -1,99E+02 -1,89E+02	8,57E-02 0,00E+00 8,56E-02 3,19E+00 0,00E+00 3,19E+00	-6,95E+01 0,00E+00 -6,95E+01 -2,40E+01 0,00E+00 -2,40E+01
	PERE PERM PERT PENRE PENRM PENRT SM		MJ MJ MJ MJ MJ	0 0 0 0 0 0	0 0 0 0 0 0	8,19E-02 0,00E+00 8,19E-02 5,80E+00 0,00E+00 5,80E+00 0,00E+00	1,24E+00 0,00E+00 1,24E+00 1,04E+01 -1,99E+02 -1,89E+02 0,00E+00	8,57E-02 0,00E+00 8,56E-02 3,19E+00 0,00E+00 3,19E+00 0,00E+00	-6,95E+01 0,00E+00 -6,95E+01 -2,40E+01 0,00E+00 -2,40E+01 0,00E+00

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009" *INA Indicator Not Assessed

Flol: l:

End of life - Waste										
	Indicator			Unit		A4	A5	B2	В3	
	HWD	HWD		kg		2,10E-03	0,00E+00	1,87E-02	8,39E-04	
⊕	NHWD		k	g	1,52E+01	3,34E+00	5,48E+00	4,24E-01	1,73E-02	
<u> </u>	RWD		k	g	3,10E-03	2,62E-04	0,00E+00	7,21E-04	3,26E-05	
In	dicator		Unit	B4	C1	C2	C3	C4	D	
	HWD		kg	0	0	2,96E-04	0,00E+00	1,16E+01	-8,52E-03	
Ū	NHWD		kg	0	0	2,77E-01	2,04E+00	3,06E-01	-8,91E-01	
æ	RWD		kg	0	0	3,96E-05	0,00E+00	1,85E-05	-5,38E-05	

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009" *INA Indicator Not Assessed

End of life - Output flow	End of life - Output flow											
Ind	icator	Un	it	A1-A3	A4	A5	B2	В3				
®▷	CRU	kç	kg		0,00E+00	0,00E+00	0,00E+00	0,00E+00				
&▷	MFR	kç	kg		0,00E+00	5,02E+00	0,00E+00	0,00E+00				
DF	MER	kç	kg		0,00E+00	7,03E-02	0,00E+00	0,00E+00				
5D	EEE	М	J	4,62E-01	0,00E+00	3,02E-01	0,00E+00	0,00E+00				
D	EET	М	J	6,99E+00	0,00E+00	4,58E+00	0,00E+00	0,00E+00				
Indicato	or	Unit	B4	C1	C2	C3	C4	D				
∅>	CRU	kg	0	0	0,00E+00	0,00E+00	0,00E+00	0,00E+00				
\$>	MFR	kg	0	0	0,00E+00	2,64E+00	0,00E+00	0,00E+00				
DV	MER	kg	0	0	0,00E+00	2,16E+01	0,00E+00	0,00E+00				
50	EEE	МЈ	0	0	0,00E+00	8,30E+00	0,00E+00	0,00E+00				
	EET	МЈ	0	0	0,00E+00	1,26E+02	0,00E+00	0,00E+00				

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9,0 E-03 = 9,0*10-3 = 0,009" *INA Indicator Not Assessed

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	1,98E+00
Biogenic carbon content in accompanying packaging	kg C	4,75E-01

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO2



Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Electricity, high voltage, hydro (kWh) - PL	ecoinvent 3.6	4,02	g CO2-eq/kWh

Dangerous substances

No substances given by the REACH Candidate list or the Norwegian priority list are intentionally added to the product.

Indoor environment

Additional Environmental Information

Additional environmental impact indicators required in NPCR Part A for construction products							
Indicator	Unit	Unit		A4	A5	B2	В3
GWPIOBC	kg CO ₂ -eq	kg CO ₂ -eq		2,47E+00	0,00E+00	5,99E+00	2,69E-01
Indicator	Unit	B4	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	0	0	3,85E-01	1,68E+01	1,93E-01	-3,10E+00

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Variants and Options

Key environmental indicators (A1-A3) for variants of this EPD				
Variants	Weight (kg)	GWPtotal (kg CO ₂ -eq)	Total energy consumption (MJ)	Amount of recycled materials (%)
giroflex 64-3078 without accessories (Camira/Xtreme) - No packaging	17,88	62,69	887,04	51,85
giroflex 64-3578 without accessories (Camira/Xtreme) - No packaging	18,15	64,84	916,96	50,93
giroflex 64-4578 without accessories (Camira/Xtreme) - No packaging	18,38	65,69	932,41	50,34
giroflex 64-4578 with extra seat depth 5cm, without accessories (Camira/Xtreme) - No packaging	18,81	66,19	954,01	49,21

Key environmental indicators (A1-A3) for options for this EPD						
Options	Weight (kg)	GWPtotal (kg CO ₂ -eq)	Total energy consumption (MJ)	Amount of recycled materials (%)		
giroflex 64 - 1D armrests	2,52	14,90	214,55	17,19		
giroflex 64 - 1D armrests upholstered	3,07	17,77	249,96	21,07		
giroflex 64 - 4D armrests set	3,52	16,16	225,79	37,11		
giroflex 64 - 4D armrests upholstered set	3,74	16,48	229,06	40,80		
giroflex 64 - Lumbar Support Deapth Adjustable	0,24	1,39	20,17	17,42		
giroflex 64 - Push Rod Cover	0,09	0,28	5,92	0,00		
giroflex 64 - Coat Hanger	0,43	1,51	21,02	15,97		
giroflex 64 - Upholstered Backshell	0,36	1,37	11,10	94,56		
giroflex 64 - Comfort Upholstery	0,37	2,58	41,64	0,09		
giroflex 64-3078 - Packaging	5,07	-1,60	153,70	83,16		
giroflex 64-35/4578 - Packaging	5,48	-1,87	162,67	84,42		

Key Environmental Indicators

Indicator	Unit	A1-A3	A4	A1-C4	A1-D
GWPtotal	kg CO ₂ -eq	79,13	2,47	115,54	113,19
Total energy consumption	MJ	1305,42	38,94	1502,35	1406,39
Amount of recycled materials	%	55,87			



Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.

ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.

EN 15804:2012 + A2:2019 Environmental product declaration - Core rules for the product category of construction products.

ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.

ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.

Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21 Ruud et al., (2023) EPD generator for NPCR026 Part B for Furniture - Background information for EPD generator application and LCA data, LCA.no report number 01.23

NPCR Part A: Construction products and services. Ver. 2.0. March 2021, EPD-Norge.

NPCR 026 Part B for Furniture. Ver. 2.0 March 2022, EPD-Norge.

and norway	Program operator and publisher	Phone:	+47 23 08 80 00
© epd-norway	The Norwegian EPD Foundation	e-mail:	post@epd-norge.no
Global Program Operator	Post Box 5250 Majorstuen, 0303 Oslo, Norway	web:	www.epd-norge.no
	Owner of the declaration:	Phone:	0047 98 25 68 30
	Flokk AS	e-mail:	atle.messel@flokk.com
1 1 0 10 10	Drammensveien 145,, 0277 Oslo	web:	https://www.flokk.com
	Author of the Life Cycle Assessment	Phone:	+47 916 50 916
(LCA)	LCA.no AS	e-mail:	post@lca.no
.no	Dokka 6B, 1671	web:	www.lca.no
	Developer of EPD generator	Phone:	+47 916 50 916
(LCA)	LCA.no AS	e-mail:	post@lca.no
.no	Dokka 6B,1671 Kråkerøy	web:	www.lca.no
ECO PLATFORM	ECO Platform	web:	www.eco-platform.org
VERIFIED	ECO Portal	web:	ECO Portal