

Test Report

Report No.: 807185-8



**DANISH
TECHNOLOGICAL
INSTITUTE**

Gregersensvej
DK-2630 Taastrup
Tel. +45 72 20 20 00
Fax +45 72 20 20 19

info@teknologisk.dk
www.teknologisk.dk

Assignor: Offecct AB
Skövdevägen
SE-543 21 Tibro

Page 1 of 1
Laha/ir/hbs
Order no.: 807185
No. of appendices: 2

Subject: Model: On Point Table - also covers Medium Model

Type:	Table			
Diameter:	Ø 1200		Height:	1100 mm
Materials:	Wood, upholstery			

Sampling: The test material was sampled by the client and received at the Danish Technological Institute 21-06-2018.

Method: EN 15372:2016 Furniture – Strength, durability and safety – Requirements for non-domestic tables.

Test level 2 General: General hotel, cafés, restaurants, public halls, banks, bars meeting rooms

Period: The testing was carried out from 25-06-2018 to 06-07-2018.

Result: Model On Point Table fulfils the requirements in EN 15372:2016, L2.

Individual results appear from Appendix 1.

Storage: The test material will be destroyed after 1 month, unless otherwise agreed.

Terms: The accredited test was carried out according to DANAK's general conditions see www.danak.dk and according to the General Terms and Conditions regarding Commissioned Work Accepted by the Danish Technological Institute, which apply at the time of signing the agreement. The test is only valid for the tested specimen. The test report may only be extracted, if the laboratory has approved the extract.

Date/place: 06-07-2018, Danish Technological Institute, Wood and Biomaterials, Taastrup

Digitally signed
Lars Jeffers-Hansen
E-mail: laha@dti.dk
Phone: +45 7220 2390

Digitally signed
Ib Rasmussen
E-mail: ir@dti.dk
Phone: +45 7220 2324

Signature: Test responsible

Co-signatory

Lars Jeffers-Hansen
Ph. direct: +45 72 20 23 90
E-mail: laha@teknologisk.dk



Order no.: 807185-8
Appendix: 1
Page: 1 of 1
Initials: Laha/ir/hbs

Test of Model: On Point Table

EN 15372:2016

Test	Test Method	Cycles	2	Result
5.1	General requirements	See Appendix 3		Passed
5.4.1 – Table:				
1	Horizontal static load test	EN 1730:2012, 6.2	Test force F_{1-4} , N: Type 1 Type 2 Min. force Type 1 and Type 2 Specified mass, kg Cycles	400 200 100 Manufacturer's specified load or 50 kg 10 Passed
2	Vertical static load test on main surface ^a	EN 1730:2012, 6.3.1	Test force, N Cycles	1.250 10 Passed
3	Additional vertical static load test where the main surface has a length >1600 mm	EN 1730:2012, 6.3.2	Test force, N Cycles	1.000 10 N/A
4	Vertical static load on ancillary surface	EN 1730:2012, 6.3.3	Test force, N Cycles	300 10 N/A
5	Horizontal durability test	EN 1730:2012, 6.4.1 and 6.4.2	Test force F_{a-d} , N Specified mass, kg Cycles	300 Manufacturer's specified load or 50 kg 15.000 Passed
6	Vertical durability test for cantilever and tables with central column only ^b	EN 1730:2012, 6.5	Test force, N Cycles	300 15.000 Passed
7	Vertical impact test for glass tabletops	EN 1730:2012, 6.6.1 and 6.6.2	Drop height, mm: Safety glass ^c Other glass Cycles	180 240 10 N/A
8	Vertical impact test for all other tabletops	EN 1730:2012, 6.6.1 and 6.6.3	Drop height, mm: Cycles	180 10 Passed
9	Drop test – This test is applicable for tables weighing more than 20 kg only	EN 1730:2012, 6.9	Nom. drop height mm – tables without glass Nom. drop height mm – tables with glass	100 50 Passed
10	Stability under vertical load test	EN 1730:2012, 7.2	Test force, N Main surface V_1 V_2 Ancillary surface V_1 V_2	200 400 100 200 Passed
11	Stability for tables with extension elements	EN 1730:2012, 7.3	Test force, N	200 N/A
^a Tables with extension pieces shall be tested both in the extended and unextended configurations. A table extension added in the centre of the table shall be tested as the main surface. A part of the main surface in the unextended configuration can become an ancillary surface in the extended configuration. ^b Examples of cantilever tables and tables with a central column are shown in EN 1730:2012, figures 6b and 6d ^c Glass is considered to be safety glass, if the glass fulfils the requirements in EN 12150-1:2015, Clause 8, fragmentation test; or where the mode of breakage (β) according to EN 12600:2002 is Type B or Type C N/A Not applicable				

Order no.: 807185-8-3
Appendix: 2
Page: 1 of 1
Initials: Laha/ir/hbs

Test of Model: On Point Table

Photo

