

Environmental product declaration

in accordance with ISO 14025 and EN 15804+A2

OFFECCT On Point



OFFECCT

Flokk

EPD-Global

Owner of the declaration:

Flokk AS

Product:

OFFECCT On Point

Declared unit:

1 pcs

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR

NPCR 026:2022 Part B for Furniture

Program operator:

EPD-Global

Declaration number:

NEPD-16939-21045

Issue date:

06.07.2026

Valid to:

06.07.2031

EPD software:

LCAno EPD generator ID: 1675828

General information

Product

OFFECCT On Point

Program operator:

EPD-Global
Post Box 5250 Majorstuen, 0303 Oslo, Norway
Phone: +47 977 22 020
web: www.epd-global.com

Declaration number:

NEPD-16939-21045

This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR
NPCR 026:2022 Part B for Furniture

Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD-Global shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

Declared unit:

1 pcs OFFECCT On Point

Declared unit (cradle to gate) with option:

A1-A3, A4, A5, B2, B3, B4, C1, C2, C3, C4, D

Functional unit:

1 pc OFFECCT On Point — Table Ø160 cm x H65 cm, upholstered in Cura fabric from Gabriel, (Cura/Gabriel), with full centre module — including packaging.

General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Verification of each EPD is made according to EPD-Global's guidelines for verification and approval requiring that tools are i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD-Global, and iii) the process is reviewed annually by an independent third party verifier. See Appendix G of EPD-Global's General Programme Instructions for further information on EPD tools

Verification of EPD tool:

Independent third party verification of the EPD tool, background data and test-EPD in accordance with EPD-Global's procedures and guidelines for verification and approval of EPD tools.

Third party verifier:

Elisabet Amat, GREENIZE projects

(no signature required)

Owner of the declaration:

Flokk AS
Contact person: Atle Thiis-Messel
Phone: 0047 98 25 68 30
e-mail: atle.messel@flokk.com

Manufacturer:

Flokk AS
Drammensveien 145,
0277 Oslo, Norway

Place of production:

Flokk - Turek
ul. Górnica 8
62-700 Turek, Poland

Management system:

ISO 14001, ISO 9001.

Organisation no:

No 928 902 749

Issue date:

06.07.2026

Valid to:

06.07.2031

Year of study:

2025

Comparability:

EPDs of construction products may not be comparable if they do not comply with EN 15804 and are not viewed in a building context.

Development and verification of EPD:

The declaration is created using EPD tool lca.tools ver EPD2022.03, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD-Global.

Developer of EPD: Damian Bakowski

Reviewer of company-specific input data and EPD: Damian Piterek

Approved:



Håkon Hauan, CEO EPD-Global

Product

Product description:

The OFFECCT On Point collection is a family of upholstered tables designed for indoor public and commercial environments, supporting informal meetings, collaborative work and social interaction. Designed by Mattias Stenberg, the collection combines a soft, elegant appearance with a functional central element, making it suitable for offices, lounges, hospitality areas, waiting zones, airports and other shared interiors where people meet, work or spend time between activities.

Product specification

The model analysed in detail in this declaration is the OFFECCT On Point — table Ø160 cm x H65 cm, upholstered in Cura fabric from Gabriel, (Cura/Gabriel), with full centre module — including packaging. Key environmental indicators (models and options) of the OFFECCT On Point tables are presented in tables on pages 11 of this declaration.

Materials	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Adhesive	0.15	0.2738	0.0001392	0.0928
High Pressure Laminate	2.02	3.69	0.00	0.00
Metal - Aluminium	0.00096	0.001752	0.00096	100.00
Metal - Steel	0.761	1.39	0.048	6.31
Metal - Zinc	0.02304	0.04206	0.0009242	4.01
Plastic - Polypropylene (PP)	0.009	0.01643	0.00	0.00
Plastic - Polyurethane (PUR)	1.24	2.27	0.0356	2.87
Printed paper	0.0002	0.0003651	0.00	0.00
Textile - Polyester	1.12	2.05	1.18	105.56
Wood - Fibreboard	7.42	13.54	0.00	0.00
Wood - Medium Density Fibreboard (MDF)	3.48	6.35	0.00	0.00
Wood - Plywood	34.56	63.09	0.1019	0.2949
Wood - Solid beech/birch	3.99	7.28	0.00	0.00
Total	54.78	100.00	1.37	

Packaging	kg	%	Recycled share in material (kg)	Recycled share in material (%)
Packaging - Cardboard	2.48	17.89	0.00	0.00
Packaging - Paper	0.005	0.03609	0.00	0.00
Packaging - Plastic	0.6576	4.75	0.001702	0.2588
Packaging - Plastic straps	0.042	0.3031	0.00	0.00
Packaging - Wood	2.15	15.52	0.00	0.00
Recycled cardboard	8.52	61.50	8.52	100.00
Total incl. packaging	68.63	100.00	9.89	

Technical data:

The collection includes four table versions and three centre module options, allowing On Point to be adapted to different spatial concepts, meeting formats and interior requirements. The central module can be used to integrate plants and greenery into the table, supporting Offecct's O2asis concept, or specified as a full centre module for a more closed tabletop expression.

Market:

Worldwide.

A4 stage transportation from factory to market, is assumed to be 1.000 km.

Reference service life, product

15 years (warranty 5 years)

Reference service life, building

N/A

LCA: Calculation rules

Declared unit:

1 pcs OFFECCT On Point

Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

Data quality:


Specific data for the product composition are provided by the manufacturer. They represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on registered EPDs according to EN 15804, Ostfold Research databases, ecoinvent and other LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Adhesive	Modified ecoinvent 3.10.1	Database	2023
High Pressure Laminate	S-P-06281	EPD	2022
Metal - Aluminium	ecoinvent 3.10.1	Database	2023
Metal - Steel	ecoinvent 3.10.1	Database	2023
Metal - Steel	Modified ecoinvent 3.10.1	Database	2023
Metal - Steel	Modified ecoinvent 3.6	Database	2019
Metal - Zinc	ecoinvent 3.10.1	Database	2023
Packaging - Cardboard	Modified ecoinvent 3.10.1	Database	2023
Packaging - Paper	ecoinvent 3.10.1	Database	2023
Packaging - Plastic	ecoinvent 3.10.1	Database	2023
Packaging - Plastic	Modified ecoinvent 3.10.1	Database	2023
Packaging - Plastic straps	ecoinvent 3.10.1	Database	2023
Packaging - Wood	ecoinvent 3.10.1	Database	2023
Plastic - Polypropylene (PP)	Modified ecoinvent 3.10.1	Database	2023
Plastic - Polyurethane (PUR)	Modified ecoinvent 3.10.1	Database	2023
Printed paper	ecoinvent 3.10.1	Database	2023
Recycled cardboard	Modified ecoinvent 3.10.1	Database	2023
Textile - Polyester	ecoinvent 3.10.1	Database	2023
Wood - Fibreboard	ecoinvent 3.10.1	Database	2023
Wood - Medium Density Fibreboard (MDF)	ecoinvent 3.10.1	Database	2023
Wood - Plywood	ecoinvent 3.10.1	Database	2023
Wood - Solid beech/birch	Modified ecoinvent 3.10.1	Database	2023

System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		Use stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	X	X	X	MND	MND	MND	X	X	X	X	X

System boundary:



Additional technical information:

LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

Transport from production place to user (A4)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, over 32 tonnes, EURO 5 (km)	55.0 %	1000.00	0.023	l/tkm	23.00
Assembly (A5)	Unit	Value			
Waste, packaging, cardboard, 100 % recycled, to average treatment (kg)	kg	8.52			
Waste, packaging, corrugated board box, 0 % recycled, to average treatment (kg)	kg	2.48			
Waste, Wood, medium density fibreboard (MDF) average treatment (kg) - A5, inkl. 85 km transp.	kg	2.15			
Waste, packaging, PET straps, to average treatment - A5 (kg)	kg	0.042			
Waste, packaging, plastic film (LDPE), to average treatment - A5 (kg)	kg	0.5826			
Waste, packaging, paper printed, to average treatment (kg)	kg	0.005			
Waste, packaging, plastic tape, to average treatment (kg)	kg	0.075			
Maintenance (B2)	Unit	Value			
Electricity, World average (kWh)	kWh	1.17			
Electricity, European average (kWh)	kWh	10.53			
Water, tap water (m3)	m3	0.78			
Repair (B3)	Unit	Value			
Electricity, World average (kWh)	kWh	0.055			
Electricity, European average (kWh)	kWh	0.495			
Transport to waste processing (C2)	Capacity utilisation (incl. return) %	Distance (km)	Fuel/Energy Consumption	Unit	Value (Liter/tonne)
Truck, 16-32 tonnes, EURO 5 (km)	38.8 %	85.00	0.045	l/tkm	3.83
Waste processing (C3)	Unit	Value			
Waste treatment per kg Wood, incineration with fly ash extraction (kg)	kg	49.45			
Waste, materials to recycling (kg)	kg	0.2583			
Waste treatment per kg Scrap steel, incineration with fly ash extraction (kg)	kg	0.761			
Waste treatment per kg Polyurethane (PU), incineration (kg)	kg	1.24			
Waste treatment per kg Textile, incineration with fly ash extraction (kg)	kg	1.12			
Waste treatment per kg Hazardous waste, incineration (kg)	kg	0.15			
Waste treatment per kg Scrap aluminium, incineration with fly ash extraction (kg)	kg	0.00096			
Waste treatment per kg Non-hazardous waste, incineration with fly ash extraction - C3 (kg)	kg	2.04			
Waste treatment per kg Polypropylene (PP), incineration with fly ash extraction - C3 (kg)	kg	0.009			
Waste treatment per kg Graphical paper, incineration with fly ash extraction (kg)	kg	0.0002			
Benefits and loads beyond the system boundaries (D)	Unit	Value			
Substitution of thermal energy, district heating (MJ)	MJ	0.06672			
Substitution of electricity (MJ)	MJ	0.2983			
Substitution of primary steel with net scrap (kg)	kg	0.2397			

LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact							
Indicator	Unit	A1-A3	A4	A5	B2	B3	
GWP-total	kg CO ₂ -eq	-2.86E+01	7.36E+00	2.11E+01	4.67E+00	2.08E-01	
GWP-fossil	kg CO ₂ -eq	6.39E+01	7.35E+00	1.23E+00	4.53E+00	2.02E-01	
GWP-biogenic	kg CO ₂ -eq	-9.32E+01	4.60E-03	1.99E+01	1.29E-01	5.84E-03	
GWP-luluc	kg CO ₂ -eq	6.82E-01	2.76E-03	9.05E-05	1.27E-02	5.77E-04	
ODP	kg CFC11 -eq	3.18E-06	1.37E-07	5.47E-09	7.25E-08	3.26E-09	
AP	mol H ⁺ -eq	4.10E-01	2.37E-02	1.23E-03	2.59E-02	1.16E-03	
EP-FreshWater	kg P -eq	2.83E-02	4.96E-04	2.35E-05	3.74E-03	1.69E-04	
EP-Marine	kg N -eq	1.33E-01	8.06E-03	6.92E-04	4.25E-03	1.89E-04	
EP-Terrestrial	mol N -eq	1.33E+00	8.77E-02	5.19E-03	3.93E-02	1.74E-03	
POCP	kg NMVOC -eq	4.31E-01	3.87E-02	1.77E-03	1.27E-02	5.60E-04	
ADP-minerals&metals ¹	kg Sb-eq	4.19E-04	2.03E-05	8.89E-07	5.27E-05	2.42E-06	
ADP-fossil ¹	MJ	1.15E+03	1.07E+02	3.58E+00	9.54E+01	4.29E+00	
WDP ¹	m ³	6.42E+01	5.46E-01	1.61E-01	2.52E+00	1.13E-01	

Indicator	Unit	B4	C1	C2	C3	C4	D
GWP-total	kg CO ₂ -eq	0	0	1.13E+00	1.03E+02	0	-1.26E-01
GWP-fossil	kg CO ₂ -eq	0	0	1.13E+00	6.23E+00	0	-1.24E-01
GWP-biogenic	kg CO ₂ -eq	0	0	8.61E-04	9.70E+01	0	-1.90E-03
GWP-luluc	kg CO ₂ -eq	0	0	3.99E-04	2.36E-04	0	-1.96E-04
ODP	kg CFC11 -eq	0	0	2.33E-08	1.98E-08	0	-2.82E-05
AP	mol H ⁺ -eq	0	0	3.53E-03	1.44E-02	0	-5.24E-04
EP-FreshWater	kg P -eq	0	0	7.48E-05	4.36E-04	0	-6.64E-05
EP-Marine	kg N -eq	0	0	1.19E-03	9.04E-03	0	-1.10E-04
EP-Terrestrial	mol N -eq	0	0	1.29E-02	7.39E-02	0	-1.12E-03
POCP	kg NMVOC -eq	0	0	5.53E-03	1.85E-02	0	-3.63E-04
ADP-minerals&metals ¹	kg Sb-eq	0	0	3.69E-06	3.23E-06	0	-6.46E-07
ADP-fossil ¹	MJ	0	0	1.58E+01	1.04E+01	0	-1.76E+00
WDP ¹	m ³	0	0	7.78E-02	2.12E+00	0	-1.74E-01

GWP-total = Global Warming Potential total; GWP-fossil = Global Warming Potential fossil fuels; GWP-biogenic = Global Warming Potential biogenic; GWP-luluc = Global Warming Potential land use and land use change; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential, Accumulated Exceedance; EP-freshwater = Eutrophication potential, fraction of nutrients reaching freshwater end compartment; EP-marine = Eutrophication potential, fraction of nutrients reaching marine end compartment; EP-terrestrial = Eutrophication potential, Accumulated Exceedance; POCP = Formation potential of tropospheric ozone; ADP-minerals&metals = Abiotic depletion potential for non-fossil resources; ADP-fossil = Abiotic depletion for fossil resources potential; WDP = Water (user) deprivation potential, deprivation-weighted water consumption

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator

Remarks to environmental impacts

The LCA results in the EPD are calculated using a specific methodological approach for accounting energy resources, see the additional requirements section for more information. In this EPD the following approach was used: Location-based approach.

Additional environmental impact indicators

Indicator	Unit	A1-A3	A4	A5	B2	B3
 PM	Disease incidence	6.91E-06	7.55E-07	2.15E-08	1.24E-07	5.17E-09
 IRP ²	kgBq U235 -eq	9.23E+00	1.28E-01	5.32E-03	2.42E+00	1.10E-01
 ETP-fw ¹	CTUe	5.91E+02	1.26E+01	4.01E+00	1.53E+01	6.81E-01
 HTP-c ¹	CTUh	2.44E-07	0.00E+00	1.14E-10	1.32E-09	6.20E-11
 HTP-nc ¹	CTUh	7.93E-07	6.86E-08	7.57E-09	8.18E-08	3.22E-09
 SQP ¹	dimensionless	7.35E+03	1.07E+02	2.04E+00	2.08E+01	9.32E-01

Indicator	Unit	B4	C1	C2	C3	C4	D
 PM	Disease incidence	0	0	8.75E-08	1.11E-07	0	-1.27E-08
 IRP ²	kgBq U235 -eq	0	0	2.02E-02	2.59E-02	0	-3.31E-02
 ETP-fw ¹	CTUe	0	0	2.08E+00	2.41E+01	0	-5.06E-01
 HTP-c ¹	CTUh	0	0	0.00E+00	2.11E-09	0	-6.28E-10
 HTP-nc ¹	CTUh	0	0	1.17E-08	9.90E-08	0	-2.14E-09
 SQP ¹	dimensionless	0	0	9.43E+00	2.45E+00	0	-5.21E-01

PM = Particulate Matter emissions; IRP = Ionizing radiation – human health; ETP-fw = Eco toxicity – freshwater; HTP-c = Human toxicity – cancer effects; HTP-nc = Human toxicity – non cancer effects; SQP = Soil Quality (dimensionless)

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.

Resource use							
Indicator		Unit	A1-A3	A4	A5	B2	B3
	PERE	MJ	1.03E+03	1.73E+00	7.66E-02	2.44E+01	1.11E+00
	PERM	MJ	8.16E+02	0.00E+00	-1.71E+02	0.00E+00	0.00E+00
	PERT	MJ	1.85E+03	1.73E+00	-1.71E+02	2.44E+01	1.11E+00
	PENRE	MJ	9.54E+02	1.07E+02	3.58E+00	9.54E+01	4.29E+00
	PENRM	MJ	2.17E+02	0.00E+00	-3.30E+01	0.00E+00	0.00E+00
	PENRT	MJ	1.17E+03	1.07E+02	-2.94E+01	9.54E+01	4.29E+00
	SM	kg	9.89E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	RSF	MJ	1.09E+01	5.81E-04	2.88E-05	1.26E-04	5.45E-06
	NRSF	MJ	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	FW	m ³	1.46E+00	1.57E-02	2.58E-03	8.58E-01	3.54E-03

Indicator		Unit	B4	C1	C2	C3	C4	D
	PERE	MJ	0	0	2.74E-01	4.01E-01	0	-6.69E-01
	PERM	MJ	0	0	0.00E+00	-7.29E+02	0	0.00E+00
	PERT	MJ	0	0	2.74E-01	-7.28E+02	0	-6.69E-01
	PENRE	MJ	0	0	1.58E+01	1.04E+01	0	-1.76E+00
	PENRM	MJ	0	0	0.00E+00	-6.58E+02	0	0.00E+00
	PENRT	MJ	0	0	1.58E+01	-6.48E+02	0	-1.76E+00
	SM	kg	0	0	0.00E+00	0.00E+00	0	-2.72E-01
	RSF	MJ	0	0	9.16E-05	8.59E-05	0	-2.72E-05
	NRSF	MJ	0	0	0.00E+00	0.00E+00	0	-2.02E-03
	FW	m ³	0	0	2.13E-03	1.96E-02	0	-4.66E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non renewable primary energy resources used as raw materials; PENRT = Total use of non renewable primary energy resources; SM = Use of secondary materials; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Net use of fresh water

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

End of life - Waste							
Indicator		Unit	A1-A3	A4	A5	B2	B3
	HWD	kg	3.99E+00	1.54E-01	1.67E-02	3.02E-01	1.30E-02
	NHWD	kg	1.57E+02	3.09E+00	2.55E+00	2.53E+01	8.25E-01
	RWD	kg	2.60E-03	3.18E-05	1.01E-06	2.19E-05	0.00E+00

Indicator		Unit	B4	C1	C2	C3	C4	D
	HWD	kg	0	0	2.27E-02	1.50E-01	0	-9.43E-02
	NHWD	kg	0	0	4.80E-01	5.46E+01	0	-2.93E-01
	RWD	kg	0	0	5.02E-06	0.00E+00	0	-8.47E-06

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

End of life - Output flow							
Indicator		Unit	A1-A3	A4	A5	B2	B3
	CRU	kg	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
	MFR	kg	8.17E-01	0.00E+00	1.18E+01	0.00E+00	0.00E+00
	MER	kg	5.68E-07	0.00E+00	8.76E-09	0.00E+00	0.00E+00
	EEE	MJ	1.59E-03	0.00E+00	2.98E-04	0.00E+00	0.00E+00
	EET	MJ	3.75E-02	0.00E+00	4.65E-04	0.00E+00	0.00E+00

Indicator		Unit	B4	C1	C2	C3	C4	D
	CRU	kg	0	0	0.00E+00	0.00E+00	0	0.00E+00
	MFR	kg	0	0	0.00E+00	6.19E-01	0	0.00E+00
	MER	kg	0	0	0.00E+00	1.25E+00	0	0.00E+00
	EEE	MJ	0	0	0.00E+00	2.95E-01	0	0.00E+00
	EET	MJ	0	0	0.00E+00	6.56E-02	0	0.00E+00

CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported energy electrical; EET = Exported energy thermal

"Reading example: 9.0 E-03 = 9.0×10^{-3} = 0.009"

Biogenic Carbon Content		
Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	2.04E+01
Biogenic carbon content in accompanying packaging	kg C	5.43E+00

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO₂

Additional requirements

Greenhouse gas emissions from the use of electricity in the manufacturing phase

The table below presents GWP_{total} values for energy resources used in the manufacturing phase (A3), calculated with both the location-based and market-based approach. This information is provided for transparency, allowing EPD users to understand the impact of these methodological choices. When applicable, information about GoOs or biogas certificate like provider, validity date and energy source can be seen in the table below. In this EPD, the following methodology was used in the main results: Location-based approach.

Electricity mix	Source	Amount	Unit	GWP _{total} [kg CO ₂ /Unit]	SUM [kg CO ₂]
Location-based approach.					
Electricity, high voltage electricity production, hydro, run-of-river (kWh) - PL	ecoinvent 3.10.1	6.64E+00	kWh	4.39E-03	2.91E-02
Market-based approach.					
Electricity, Poland, low voltage, residual mix	ecoinvent 3.10.1	6.64E+00	kWh	1.10E+00	7.27E+00

"Reading example: 9.0 E-03 = 9.0*10⁻³ = 0.009"

Dangerous substances

The product contains no substances given by the REACH Candidate list.

Indoor environment

Möbelfakta

Additional Environmental Information

Key Environmental Indicators

Key environmental performance indicators	Unit	Product stage	Construction stage		Use stage			End-of-life				Net benefits and loads from reuse, recovery, and/or recycling
		A1-A3	A4	A5	B2	B3	B4	C1	C2	C3	C4	D
GWP _{total}	kg CO ₂ -eq	-28.65	7.36	21.13	4.67	0.21	0.00	0.00	1.13	103.19	0.00	-0.13
Total energy consumption	MJ	1999.52	108.25	3.66	119.78	5.40	0.00	0.00	16.12	10.76	0.00	-2.43
Share of recycled materials	%	14.41										

Additional environmental impact indicators required in NPCR Part A for construction products

Indicator	Unit	A1-A3	A4	A5	B2	B3
GWPIOBC	kg CO ₂ -eq	6.56E+01	7.36E+00	1.23E+00	4.55E+00	2.03E-01

Indicator	Unit	B4	C1	C2	C3	C4	D
GWPIOBC	kg CO ₂ -eq	0	0	1.13E+00	6.23E+00	0	-1.24E-01

GWP-IOBC: Global warming potential calculated according to the principle of instantaneous oxidation. In order to increase the transparency of biogenic carbon contribution to climate impact, the indicator GWP-IOBC is required as it declares climate impacts calculated according to the principle of instantaneous oxidation. GWP-IOBC is also referred to as GWP-GHG in context to Swedish public procurement legislation.

Variants and Options

Key environmental indicators (A1-A3) for variants of this EPD

Variants	Weight (kg)	GWP _{total} (kg CO ₂ -eq)	Total energy consumption (MJ)	Amount of recycled materials (%)
OFFECCT On Point — Table Ø160 cm x H65 cm, upholstered (Cura/Gabriel), w/o centre module — No Packaging	51.65	-23.41	1568.63	2.64
OFFECCT On Point — Table Ø160 cm x H72 cm, upholstered (Cura/Gabriel), w/o centre module — No Packaging	52.97	-24.88	1600.14	2.47
OFFECCT On Point — Medium table Ø120 cm x H90 cm, upholstered (Cura/Gabriel), w/o centre module — No Packaging	36.00	-13.23	1064.19	3.41
OFFECCT On Point — High table Ø120 cm x H110 cm, upholstered (Cura/Gabriel), w/o centre module — No Packaging	40.49	-16.59	1173.78	3.05

Key environmental indicators (A1-A3) for options for this EPD

Options	Weight (kg)	GWP _{total} (kg CO ₂ -eq)	Total energy consumption (MJ)	Amount of recycled materials (%)
OFFECCT On Point — Full centre module for plants, Ø 50 cm, HPL laminated	3.13	-1.73	100.53	0.26
OFFECCT On Point — Open centre module for plants, Ø 50/38 cm, lacquered	1.25	-0.58	18.40	0.06
OFFECCT On Point — Open centre module for plants, Ø 50/14.5 cm, lacquered	2.84	-1.39	41.42	0.05
OFFECCT On Point — Packaging	13.85	-3.61	329.24	61.74

Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.
 ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.
 EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.
 ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.
 ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.
 Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21
 Ruttenborg et al., (2025) EPD generator for NPCR026 Part B for Furniture - Background information for EPD generator application and LCA data, LCA.no report number 08.25
 NPCR Part A: Construction products and services. Ver. 2.0. March 2021, EPD-Norge.
 NPCR 026 Part B for Furniture. Ver. 3.0 October 2024, EPD-Norge.

 epd-global Powered by EPD-Norway	Program operator and publisher EPD-Global Postboks 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 977 22 020 e-mail: post@epd-norge.no web: www.epd-global.com
	Owner of the declaration: Flokk AS Drammensveien 145,, 0277 Oslo, Norway	Phone: 0047 98 25 68 30 e-mail: atle.messel@flokk.com web: https://www.flokk.com
	Author of the Life Cycle Assessment LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	Developer of EPD generator LCA.no AS Dokka 6A, 1671 Kråkerøy, Norway	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	ECO Platform ECO Portal	web: www.eco-platform.org web: ECO Portal