

Flokk Røros
Sundveien 201
7374 Røros
Norway

Fürth, 26 August 2025

TEST REPORT No. FUHLFP2025-03035

Date sample received: 15 May 2025
Period of testing: 15 May 2025 – 26 August 2025
Technical Director: Kerstin Scharrer

Test Item: Conference / Visitor chair "Trillo Pro HST"

Test: Safety test to obtain GS mark

Determination:

The conference chair, model "Trillo Pro 21HST " has been tested for mechanical safety according to GS-mark, EN 16139 (test level 1) and the current state of the art were an essential part of the test scope. The model "21HST" does feature the same construction as the model "20HST" and therefore the test results can be validated for both models.

In summary, the mechanical safety requirements were **met** by the "Trillo Pro 21HST" and "Trillo Pro 20HST" conference chair.

NOTE: The accessibility and choice of materials are not posing a PAH-risk (see document AfPS GS 2019:01 PAK), see test report FUHLFP2025-03035-PAH.

Technical data and results as well as detailed test conditions and requirements are contained in the following pages.

Reviewed by:

Intertek Consumer Goods GmbH



Laborleitung Hardlines / Lab Manager Hardlines
Frank Urbich

Tested by:

Intertek Consumer Goods GmbH



Sachverständiger / Technical Expert
Anh Vu (Vincent) Nguyen

Product identification:

Test sample:	Conference / Visitor
Model name:	Trillo Pro 21HST
Item number:	--
Manufacturer:	Flokk sp.z.o.o UL Górnica 8 62-700 Turek Poland
Number of test samples:	1
Distributor:	Flokk AS
Delivered on:	15.05.2025
Delivered by:	Flokk sp.z.o.o

Product documents:

Instructions for use
PAH-Evaluation Report FUHLFP2025-03035-PAH

Scope of the investigations:

- EN 16139:2013 + AC:2013- Furniture - Strength, durability, and safety - Requirements for non-domestic seating.
- Tests and evaluations according to AfPS GS 2019:01 PAK

Legend:

Abbreviations:

* = Test method is not part of the accreditation scope
** = Outsourcing
n.a. = not applicable
n.t. = not tested
n.d. = not determinable (< LoQ)
LoQ = limit of quantification
CS = Combined sample
P = passed
F = failed

Applicability of test results:

Tolerances unless otherwise specified the following tolerances apply:
The tests specify the use of forces. However, masses may be used. In that case, as equivalent for 10 N a mass 1 kg can be calculated.
The test results refer solely to the samples tested.
The digital pictures shown in this report are for additional information only and are not part of this report.

Test equipment list

The test equipment list contains a list of the measuring tools used and measuring equipment, gauges, templates and load weights that were used in accordance with the scope of the investigations.

Testing machines and devices as well as any connections that are necessary for the performance of tests are not an integral part of the test equipment list.

The following test equipment were available for testing in accordance with the scope of the investigations:

Clause	Test equipment	Equipment no.
General test	Ruler	PM_HL_18.321
General test	Scale	PM_HL_18.314
General test	Band ruler 3000 mm	PM_HL_18.376
General test	Calliper	PM_HL_17.070
Strength and durability test	Load cell 5 kN	PM_HL_18.358
Strength and durability test	Load cell 5kN	PM_HL_18.359
Strength and durability test	Load cell 5kN	PM_HL_18.360
Strength and durability test	Load cell 5 kN	PM_HL_18.361
Strength and durability test	Load cell 2 kN	PM_HL_18.362
Strength and durability test	Load cell 5,5 kN	PM_HL_18.363
Strength and durability test	Seat dummy	PM_HL_18.199
Stability	Pull-Push-Gauge	PM_HL_17.026
Stability	Stability Table	PM_HL_18.107
Stability	Protractor	PM_HL_18.226
Stability	Stamp	PM_HL_18.108
Stability	Armrest stamp	PM_HL_18.051
Stability	Load disc 10 Kg	PM_HL_18.234
Stability	Load disc 10 Kg	PM_HL_18.233
Stability	Load disc 10 Kg	PM_HL_18.235
Stability	Load disc 10 Kg	PM_HL_18.238
Stability	Load disc 10 Kg	PM_HL_18.230
Stability	Load disc 5 Kg	PM_HL_18.369
Stability	Load disc 2,5 Kg	PM_HL_17.345
Stability	Load disc 0,5 Kg	PM_HL_18.263
Stability	Load disc (wood)	PM_HL_18.216
Stability	Load disc (wood)	PM_HL_18.217
Stability	Load disc (wood)	PM_HL_18.218
Stability	Load disc (wood)	PM_HL_18.219
Stability	Load disc (wood)	PM_HL_18.220
Stability	Load disc (wood)	PM_HL_18.221
Stability	Load disc (wood)	PM_HL_18.222
Stability	Load disc (wood)	PM_HL_18.223
Stability	Load disc (wood)	PM_HL_18.224
Stability	Load disc (wood)	PM_HL_18.225

Clause	Test equipment	Equipment no.
Stability	Load disc (wood)	PM_HL_18.226
Stability	Load disc (wood)	PM_HL_18.227
Stability	Load disc (wood)	PM_HL_18.228
Stability	Load disc (wood)	PM_HL_18.229
Loading point template - A-B	Measurement template	PM_HL_18.109

General Testing

Technical characteristics

General dimensions

Parameters	20HST	21HST
Depth (mm):	770	770
Height (mm):	910	910
Width (mm):	770	770
Net weight (kg):	13.2	13.7

Product description:

Visitor chair TrilloPro HST with following features:

Seat height is fixed

Synchronous seat inclination

Backrest made from plastic or with upholstered backrest pad

Armrests fixed in height

Aluminum base

4 castors made of plastic, type hard or soft with brake, optional glides

Photo documentation:





Technical Tests

Test method/Requirements	Test parameter/Results	Verdict
Strength, durability, and safety according to EN 16139:2013, Level 1 Safety The seating shall be so designed, that the injury risk of the user is minimized. All accessible components shall be so designed, that a physical injury and other hazards are avoided. This requirement is fulfilled, if: a) all accessible corners are rounded or chamfered; b) the edges of the seat, back and armrest which the user is in contact with during sitting, are rounded or chamfered; c) the edges of the handles in direction of the application are rounded or chamfered; d) all other edges are free of burrs, rounded or chamfered e) ends of hollow tubulars are covered or capped. Movable and adjustable components are so designed, that injuries and unintended operation are avoided. No load bearing component of the seating shall get loosened which is intended to be rigid. All components, which are lubricated for a better gliding, shall be so designed, that the user is protected against soiling during intended use.	All accessible corners are rounded and chamfered mentioned edges are rounded or chamfered No handle No burrs Open hollow tubulars components are covered No moveable nor adjustable parts No loosened load bearing component Protected against soiling	P P n.a. P P P P P
Note: None		

Test method/Requirements	Test parameter/Results	Verdict
4.2 Shear and squeeze points 4.2.1 Shear and squeeze points when setting up and folding Unless 4.2.2 or 4.2.3 are applicable, shear and squeeze points that are created only during setting up and folding, including tipping seat actions, are acceptable, because the user can be assumed to be in control of his/her movements and to be able to cease applying the force immediately upon experiencing pain. The edges of parts moving relative to each other and creating shear and squeeze points shall be as specified in 4.1.	No setting up or folding	n.a.
4.2.2 Shear and squeeze points under influence of powered mechanism With the exception of tipping seats there shall be no shear and squeeze points created by parts of the seating operated by powered mechanisms, e.g. springs and gas lifts.	No shear and squeeze point	P
4.2.3 Shear and squeeze points during use There shall be no shear and squeeze points created by forces applied during normal use as well as during normal movements and actions	No shear and squeeze point during use	P
Stability The seating shall not overturn under the following conditions:		
a) by pressing down on the front edge of the seat surface in the median plane;	No overturn	P
b) by applying a load on the seat surface via the front corner;	No overturn	P
c) by leaning sideways on an item of seating with or without arm rests;	No overturn	P
d) by leaning against the back rest;	No overturn	P
e) by sitting on the front edge of the seat;	No overturn	P
f) by loading the foot rest.	No footrest	n.a.
The requirement is considered to be met if the seating complies with EN 1022:2023.		
Note: None		

Intertek Consumer Goods GmbH	Tel.: +49 911 95035841	Location Fürth	General Manager
Würzburger Straße 152	Fax: +49 911 95036640	Local Court Fürth, HRB 5756	Ross McCluskey
90766 Fürth, Germany	cg.germany@intertek.com	VAT DE169317871	

Table 1: Safety, strength and durability tests

Test	EN 1728	Loading ^a	Level 1	Verdict
Seat and back static load test	6.4	Seat Back	10 times with 1.600 N 10 times with 560 N	P P
Static load test	6.5	Seat front edge	10 times with 1.300 N	P
Vertical static load on back ^b	6.6	Seat load Back	1.300 N 10 times with 600 N	P
Static load test	6.8	Foot rest/leg rest	10 times with 1.300 N	n.a.
Sideways static load test	6.10	Arm rests	10 times with 400 N	P
Downwards static load test	6.11	Arm rests	5 times with 750 N	P
Vertical upwards static load	6.13	Seat load Arm rests	250 N 10 times	P
Seat and back durability test	6.17	Seat Back ^c	100.000 cycles with 1.000 N 100.000 cycles with 300 N	P P
Durability test	6.18	Seat front edge	50.000 cycles with 800 N	P
Durability test	6.20	Arm rests	30.000 cycles with 400 N	p
Durability test	6.21	Foot rest / leg rest	50.000 cycles with 1.000 N	n.a.
Leg forward static load test	6.15	Seat load Legs	1.000 N 10 times with 500 N	p
Leg sideways static load test	6.16	Seat load Legs	1.000 N 10 times with 400 N	p
Seat impact test	6.24	Drop height	10 times of 240 mm	P
Back impact test	6.25	Height of fall Fall angle	10 times of 210 mm or 10 times of 38°	P
Arm impact test	6.26	Height of fall Fall angle	10 times of 210 mm or 10 times of 38°	p
Drop test (multiple seating)	6.27.1	Drop height	2 x 5 times of 450 mm ^d	n.a.
Static load test	6.14	Auxiliary writing surface	10 times with 300 N	n.a.
Durability test	6.22	Auxiliary writing surface	10.000 cycles with 150 N	n.a.

^a Seat load on parts not undergoing test: 750 N.

^b The test is only applicable for chairs without head/neck rest and for chairs with a height of the backrest < 1 000 mm above ground

^c No minimum force defined

^d only level 2

Test	EN 1728	Loading	Level 1	Verdict
Drop test for stacking seating	6.27.1	Drop height	10 times of 210 mm	n.a.
Backward fall test	6.28	cycles	5	n.a.
Drop test from the height of a table	6.27.3	Front leg: Rear leg:	5 times with 600 mm 5 times with 600 mm	n.a. n.a.

Table 2: Measurement table according to ANNEX C

Measurement range	Symbol						Measured value	Verdict
		allowed (-)	Min.	Max.	allowed (+)	Min. range		
Seat height and sitting height fixed	a	no	400	500	no	/	456	P
Seat height and sitting height adjustable		yes	420	480	yes	/	--	n.a.
Depth of the seat	b	yes	380	470	yes	/	422 mm	P
Seat pad width	d	no	400	-	yes	/	464 mm	P
Distance between arm rests	r	no	460	-	yes	/	499 mm	P

Table 3: Loads, Masses and Cycles of stability tests

Test description	Loads	Result	Cycles	Verdict
Overturning over the front corner	$M_1 = 30 \text{ kg}$	300 N	1	P
Overturning over the front edge	$F_1 = 600 \text{ N}$ $F_2 = 20 \text{ N}$	$F_2 > 50 \text{ N}$	1	P
Overturning over the front edge for seating with footrest	$F_1 = 600 \text{ N}$ $F_2 = 20 \text{ N}$	--	1	n.a.
Overturning over the side edge for seating without armrests	$F_1 = 600 \text{ N}$ $F_2 = 20 \text{ N}$	--	1	n.a.
Overturning over the side edge for seating with armrests	$F_1 = 250 \text{ N}$ $F_2 = 350 \text{ N}$ $F_3 = 20 \text{ N}$	$F_3 > 50 \text{ N}$	1	P
Overturning backwards for seating with backrest inclination	$F_1 = 600 \text{ N}$ $F_2 =$ If seating Height < 720 mm (0,2857 * (1 000 - Seating height in mm) If seating height > 720 mm $F_2 = 158 \text{ N}$	$F_2 > 250 \text{ N}$	1	P
tilting backrest	13 load discs	13 load discs	1	P

Test method/Requirements	Test parameter/Results	Verdict
User manual The user manual has to be provided in the language of the country, in which the seating is distributed to the end-user. It shall contain at least the following information: a) Intended use; b) Instructions for the use of adjustment features, if applicable c) Assembling instruction, if applicable; d) Maintenance instructions; e) If the chair is equipped with castors: Instructions on the choice of castors related to the floor covering; f) If the chair is equipped with an energized seat height adjustment feature an additional information is required, that only trained professionals may change or repair the energized seat height adjustment feature.	Requirements met Chairs available by specialist shop office available no assembly required across homepage no castor no height adjustment feature	P P P P n.a. n.a.
Note: None		

General note:

This report has been prepared for the titled project or named part thereof and should not be relied upon or used for any other project without an independent check being carried out as to its suitability and prior written authority of Intertek being obtained. Intertek accepts no responsibility or liability for the consequences of this document being used for a purpose other than the purposes for which it was commissioned. Any person using or relying on the document for such other purposes agrees and will by such use or reliance be taken to confirm his agreement to indemnify Intertek for all loss or damage resulting therefrom. Intertek accepts no responsibility or liability for this document to any party other than the person by whom it was commissioned.

We would like to point out, that Intertek can't provide legally binding assessments referring to isolated cases. The individual legal advice in Germany is reserved to the legal advisory professions and a binding interpretation is subject to the court of justice.

Copying excerpts or otherwise reproducing parts of the test report is permitted only with the consent of the laboratory accepting the order. This report pertains only to the test item(s).

All testing requests are subject to our Terms and Conditions available on www.intertek.com.

END OF REPORT