



RH NEW LOGIC

An RH chair is the perfect work tool, a chair that puts you in an optimal position all day, every day. A few simple adjustments is all it takes to make your RH chair fit your individual anatomy. RH chairs support an upright posture and active sitting, increasing your performance.

Ergonomics

Providing complete support in any working position, enabling you to always sit correctly and breathe properly.

- The seat has rounded front and waterfall edge to reduce pressure on thighs. The depth of the seat can be adjusted separately.
- Sculptured shape provides comfort, keeps the back upright and gives support in any position. The pronounced "Tvedt cushion" encourages movement, upright position and open posture.
- Separately adjustable backrest angle for support in any position. Defined support for the lower back and with inflatable lumbar pump as standard.
- Pictograms on all handles and levers make the chair easy to use, easy to understand. The controls can be accessed even when seated.
- Comfort layer as standard gives increased comfort feel.
- Frictional tilt mechanism follows your every movement, easily lockable in any chosen position. The tilt resistance is quickly adjustable from 40kg – 150 kg in 7 turns.
- Armrests are optional and adjustable (height, width, depth and turnable) The optional neck rest can be adjusted in height and depth.
- Easily interchangeable seat and back that can be clicked on and off.

Quality

- 10 year guarantee

Flokk is certified in accordance to:

- ISO 9001
- ISO 14001

RH New Logic is certified in accordance to:

- EN 1335-1-2-3 Class A
- Möbelfakta
- BS 5459-2
- ANSI/BIFMA X5.1
- NPR 1813

Environment

- Supports companies' environmental profile and credibility (CSR) - Cradle to cradle proof
- Easy to disassemble and no glue or harmful chemicals
- EPD(ISO14025)
- The Nordic Swan
- GREENGUARD

Design

Materials and surfaces communicating comfort and wellbeing through bodyfitting forms. Expressing human performance.

Fire classifications

Foams and standard fabrics are tested to BS/EN 1021-1&2 (cigarette & match). Foam and fabric according to BS-5852 ignition source 5 (crib 5) can be delivered on request. Please contact our customer service for further information.

Maintenance

Vacuum clean the chair with a furniture brush or wipe it with a clean cloth or sponge slightly dampened with lukewarm clean water. Do not remove any plastic parts or attempt to open the seating mechanism. Contact your Flokk dealer if the chair requires servicing or maintenance.

See flokk.com/rh for RH New Logic interactive user instruction guide.



RH NEW LOGIC

RH NEW LOGIC
200



RH NEW LOGIC
220



| MEASUREMENTS | RH NEW LOGIC 200 | RH NEW LOGIC 220 |
|---|------------------|------------------|
| Seat depth with seat slide | 380-480 mm | 380-480 mm |
| Seat depth | 475 mm | 475 mm |
| Seat width | 470 mm | 470 mm |
| Seat height - standard gas stem | 388-520 mm | 388-520 |
| Seat angle adjustment | +6.1°/-16.9° | +6.1°/-16.9° |
| Height of lumbar support above the seat | 143-241 mm | 133-231 mm |
| Backrest height | 540 mm | 630 mm |
| Backrest height adjustment (from seat) | 575-675 mm | 575-675 mm |
| Backrest width | 430 mm | 430 mm |
| Back angle adjustment | 20.6° | 20.6° |
| Height of armrest above seat | 195-310 mm | 195-310 mm |
| Distance between armrests | 320-512 mm | 320-512 mm |
| Diameter of base | 670 mm | 670 mm |

OPTIONS

Neck rest Fabric
 Neck rest Leather
 Armrest 8L upholstered top, standard black leather
 Armrest 8L upholstered top, other colors leather
 Armrest 8L top in TPU
 Uniform upholstery back and seat
 Upholstered back shell
 Decorative stitching (only for standard model)

Coat Hanger
 Base 5T Polished
 Castor for hard floors
 Castor lockable
 Coccyx seat
 XL seat
 Seat with Memory foam Q3 (available Q3 2019)

GAS STEMS

Gas steam 4T Black
 Gas steam B Black
 Gas steam A Black

For other options see the RH Price List.

The design and specifications of RH Chairs' products are developed on an ongoing basis and the above formulations should not be perceived as completely final.