



DESIGNED FOR HUMAN PERFORMANCE

RH SECUR24

An RH chair is the perfect work tool, a chair that puts you in an optimal position all day, every day. A few simple adjustments are all it takes to make your RH chair fit your individual anatomy. RH 24/7 Chairs provides unconditional support 24 hours, 7 days a week, 365 days a year.

The RH Secur24 is extremely robust, comfortable and developed for 24/7 use in control centers and observation workstations. The RH Secur24 provides maximum support and seating comfort for long, concentrated work.

Ergonomics

- Extra thick ergonomically shaped seat- and back cushions. The seat is 11 cm thick sliding seat depth adjustment (standard for Exclusive model). With the sliding seat the chair can easily be adjusted to fit users of various heights.
- Ergonomically shaped backrest with large angle of inclination
- Adjustable lumbar support, easily operated on the side of the back rest.
- Easy and simple to adjust to individual needs. All adjustment levers are easily accessible. Controls on both sides for both left and right side.
- Provided with tilting mechanism for dynamic seating, the seat of the chair follows your seating position. Robust steel construction, a hardened steel block and tilting mechanism, specially developed 24/7 seating.
- Wide range of option to suit special needs and customization of the chair.
- Various option of adjustable armrests with different functionalities e.g, height, depth, angle,
- Comfortable and adjustable headrests are optional but strongly recommended
- Special additional options such as: coat hanger, hygiene accessories, protection covers, "weapon recess" (to provide extra space and seated comfort for personnel carrying weapons, batons, hand cuffs etc)

Quality

- 3 year warranty

Flokk is certified in accordance to:

- ISO 9001
- ISO 14001

RH Secur24 is certified in accordance to:

- EN 1335
- BS 5459-2
- GS

Environment

- LGA pollutant tested (eco-label emission and harmful substances)

Fire classifications

Foams and standard fabrics are tested to BS/EN 1021-1&2 (cigarette & match). Foam and fabric according to BS-5852 ignition source 5 (crib 5) can be delivered on request. Please contact our customer service for further information.

Maintenance

Vacuum clean the chair with a furniture brush or wipe it with a clean cloth or sponge slightly dampened with lukewarm clean water. Do not remove any plastic parts or attempt to open the seating mechanism. Contact your Flokk dealer if the chair requires servicing or maintenance.



Control room
or 24/7 use

RH SECUR24

RH SECUR24 Exclusive



MEASUREMENTS

Seat depth with slide	375-515 mm (optional)	375-515 mm
Seat depth	436 mm	436 mm
Seat width	410 mm	410 mm
Seat height - standard gas stem	400-520 mm	400-520 mm
Seat angle adjustment	+4,8° / - 13,9°	+4,8° / - 13,9°
Height of lumbar support above the seat	150-300 mm	150-300 mm
Backrest height	829 mm	829 mm
Backrest width	481 mm	481 mm
Back angle adjustment	18,4°	18,4°
Height of armrest above seat	247 mm (8F)	247 mm (8F)
Distance between armrests	485 mm (8F)	485 mm (8F)
Diameter of base	710 mm	710 mm
Weight	37,6 kg	37,6 kg

OPTIONS

Headrest:	Height and angle adjustable	Weapon recess in back cushion
Headrest Exclusive:	Height, angle - and depth adjustable	Forward placed weight setting (+7 cm) for counter-pressure
Armrest 8SC:	Height, depth, width, angle adjustable	Holster protect, extra upholstery in leather or fabric
Armrest 8SC XL:	Extra large top. Height, depth, width, angle adjustable	Protection covers for headrest, back or seat cushion
Armrest 8F:	Flip able and adjustable in angle	Hygienic covers
Armrest 8H:	Flip able, height and adjustable in angle	Base in polished or black aluminium
Coat hanger:	Black coated	Castors for hard or soft floors

GAS STEMS - SEAT HIGH

ON-4S	400-530 mm (Standard)
ON-4FZ	440-590 mm
ON-4FH	490-640 mm

For other options see the RH Price List.

The design and specifications of RH Chairs' products are developed on an ongoing basis and the above formulations should not be perceived as completely final.

Dimensions refer to EN 1355-1:200